Veröffentlichungsnummer JP6206932 (A) Veröffentlichungsdatum: 1994-07-26

Erfinder: UEDA TAKASHI: KASHIWA NORIO

Anmelder: MITSUI PETROCHEMICAL IND

Klassifikation:

- Internationale: C08F4/02; C08F4/60; C08F4/654; C08F10/00: C08F4/00: C08F10/00:

(IPC1-7): C08F10/00; C08F4/02;

C08F4/654

- Europäische:

Anmeldenummer: JP19930319197 19931126 Prioritätsnummer(n): JP19930319197 19931126

INPADOC Patentfamilie anzeigen Liste der Anführungen anzeigen

Datenfehler hier melden

Zusammenfassung von JP 6206932 (A)

PURPOSE: To obtain an olefin polymer having large melt tension and large melt viscosity ratio in good reproducibility of quality and high efficiency by polymerizing an olefin in the presence of a catalyst containing a reaction product of a specific Mg compound and a Ti compound, an organoaluminum compound and a halogen compound.: CONSTITUTION:An olefin (e.g. propylene) is polymerized or copolymerized in the presence of a catalyst formed from (A) a titanium catalyst component consisting essentially of titanium, halogen and magnesium, being a mutual reaction product of a magnesium compound expressed by the formula [R

and R are hydrocarbon; X is halogen; 0>=n<=2; 0&lt;m; (OR+R&lt:1&gt:OH)/Mg [molar ratio]&gt:=1] and a halogen-containing titanium compound component and satisfying the formula OR&lt:2&gt:/Ti&lt:=0.25 (R<2&gt; is R+R&lt;1&gt;), (B) an organoaluminum compound (e.g. triisobutylaluminum) and, as necessary, (C) a halogen compound (e.g. ethylene dichloride) other than the component A and the component B to provide the

objective polymer.

Auch veröffentlicht

JP2584189 (B2)